

flexible hoses



altecnic
Caleffi group

flexible hoses

Altecnic are able to offer a full range of flexible hoses for applications including potable water, fan coil units, anti-vibration mountings, fuel oil and general applications where the benefits of using a flexible connection outweighs traditional rigid pipework.

Altecnic has a wide range of flexible hoses to suit all applications ranging from the ACV stainless steel hoses for general domestic and commercial applications to flexible tap connectors and braided oil line hoses.

The hoses detailed are just part of the range available from Altecnic.

flexible tap connector



oil lines and flexible hoses



Dimensions

flexible tap connectors

Code	Bore	Length	Connection 1	Connection 2
PA-252 B42 B13 0300	9	300	½" f swivel	15mm comp
PA-252 B42 B13 0450	9	450	½" f swivel	15mm comp
PA-252 236 B52 0300	9	300	¾" f swivel	22mm comp

Flexible tap connector hoses are intended for domestic applications on potable water applications.

Max. working pressure: 10 bar
Temperature range: -5°C to 90°C

oil lines and flexible connectors

Code	Bore	Length	Connection 1	Connection 2
PA-609 772 772 0500	7.5	500	¼" f swivel	¼" f swivel
PA-609 772 772 0600	7.5	600	¼" f swivel	¼" f swivel
PA-609 772 772 0700	7.5	700	¼" f swivel	¼" f swivel
PA-609 772 772 1000	7.5	1000	¼" f swivel	¼" f swivel
PA-609 806 779 0600	7.5	600	¼" m	¾" f swivel angle
PA-609 806 779 0750	7.5	750	¼" m	¾" f swivel angle
PA-609 806 779 1000	7.5	1000	¼" m	¾" f swivel angle
PA-609 829 772 0900	7.5	900	¼" f swivel angle	¼" f swivel
PA-609 806 829 1000	7.5	1000	¼" m	¼" f swivel angle
PA-609 806 829 0500	7.5	500	¼" m	¼" f swivel angle
PA-609 806 829 0700	7.5	700	¼" m	¼" f swivel angle

These hoses are designed for use with 28 sec grade of fuel oils.

Max. working pressure: 10 bar
Temperature range: -5°C to 90°C

Altecnic recommend replacing hoses regularly every 2 years.

ACV flexible connectors

Code	Bore	Length	Connection 1	Connection 2
PA-639 292 913 0300	13	300	½" m	¼" f swivel
PA-639 292 913 0450	13	450	½" m	¼" f swivel
PA-639 292 292 0300	13	300	½" f swivel	¼" f swivel
PA-639 322 913 0300	13	300	½" f swivel angle	½" m
PA-639 292 324 0300	13	300	½" f swivel	15mm comp
PA-639 322 324 0300	13	300	½" f swivel angle	15mm comp
PA-639 296 324 0300	13	300	¾" f swivel	15mm comp
PA-646 296 963 0300	19	300	¾" m	¾" f
PA-646 296 963 0450	19	450	¾" m	¾" f
PA-268 D03 D51 0300	16	300	¾" f swivel	22mm comp
PA-659 402 412 0300	25	300	1" m	1" f swivel
PA-659 448 449 0300	32	300	1¼" m	1" f swivel
PA-679 453 453 0300	40	300	1½" m	1" f swivel
PA-685 461 462 0300	50	300	2" m	1" f swivel*

These hoses are intended for domestic and commercial applications

Max. working pressure: 15 bar (unless stated)
Temperature range: -5°C to 90°C

E & O.E

Altecnic Ltd Mustang Drive, Stafford, Staffordshire ST16 1GW

T: +44 (0)1785 218200 E: sales@altecnic.co.uk

Registered in England No: 2095101

altecnic.co.uk

AL 082 07-03-16

altecnic
Caleffi group