

flexible hoses

for fuel oil



altecnic
Caleffi group

flexible hoses for fuel oil

Altecnic are able to offer a full range of flexible hoses for 28 sec grade fuel oil applications where the benefits of using a flexible connection out weighs traditional rigid pipework.

The hoses detailed are just part of the range available from Altecnic.

oil lines and flexible hoses



oil lines and flexible connectors

Code	Bore	Length	Description
PA-603 741 715 0900	7.5	900	CF C $\frac{1}{4}$ x MG C $\frac{1}{4}$ x 900MM
PA-609 726 705 0770	7.5	770	ST6 MC $\frac{1}{4}$ x FC $\frac{1}{4}$ x 770MM
PA-609 714 707 0900	7.5	900	ST6 MG $\frac{1}{4}$ C90 x F $\frac{3}{8}$ x 900MM
PA-609 714 705 0900	7.5	900	ST6 MG $\frac{1}{4}$ C90 x FC $\frac{1}{4}$ x 900MM
PA-609 705 740 0900	7.5	900	ST6 FC $\frac{1}{4}$ x CFC $\frac{1}{4}$ x 770MM
PA-609 705 705 0760	7.5	760	ST6 FC $\frac{1}{4}$ x FC $\frac{1}{4}$ x 760MM

Suitable for use with 28 sec grade of fuel oils.

Max. working pressure: 10 bar

Temperature range: -5°C to 90°C

Altecnic recommend replacing hoses regularly every 2 years.

E & O.E

Altecnic Ltd Mustang Drive, Stafford, Staffordshire ST16 1GW

T: +44 (0)1785 218200 E: sales@altecnic.co.uk

Registered in England No: 2095101

altecnic.co.uk

AL 248 09-03-16

altecnic
Caleffi group